Appl. No. 10/038,380 Amdt. dated December 21, 2001

AMENDMENTS TO SPECIFICATION:

Note: Amendments to specification are to be made by presenting replacement paragraphs, sections or a substitute specification marked up to show changes made relative to the immediate prior version, as set out in 37 CFR 1.121(b). The changes should be shown by strikethrough (for deleted matter) or underlining (for added matter). The amendments to the specification shall be presented only one time, and will not appear in successive amendment documents

A device for sealing a door or window casing by means for an insectrepellent gauze screen. The device comprises a rectangular insect-repellent gauze screen that is secured with one end to a roller rod, around which it can be wound and unwound, and with the other end to a pulling beam, which is provided with two handles. The roller rod is accommodated in a first frame section to be placed vertically. The pulling beam can be slid against a second frame section to be placed opposite the first frame section. The device further comprises a third and a fourth frame section, which possess a Ushaped guide section, in which an edge of the gauze screen in guided. The device comprises securing means so as to enable the fitting of the frame sections before the casing. The securing means are mounted on an inner wall of the casing, in particular on the transverse side of decorative parts present around the casing. A retractable screen for sealing an opening of a door or window casing having decorative parts on opposite sides of the opening, the screen being provided at one end with a pulling bar and having an opposite end attached to a roller rod disposed in a housing mounted to the side wall of a decorative part on one side of the opening provided with a pulling beam and, further, a receiving section for receiving the pulling beam and having a securing edge mounted to the side of the opposing decorative part.

